



Product Overview

TTECH RJ 11 patch panels support both T568A and T568B wiring schemes and can be terminated with an industry standard 110 or Krone installation tools. It is designed to 22-26 AWG solid conductor cable.

Features

- Firm and easy installation reducing the installation and operation cost
- Space for additional marking
- Rear cable management for proper and convenience cable management
- Standard is 19" rack mount type, 21" is available upon request.
- 24 Port in 1U and 48 Port in 2U
- Meet or exceed the current T568A and T568B standard

Specifications

Electrical	
Current Rating	1.5 A max
Voltage rating	150 V
Contact resistance	20 mohm
Insulation Resistance:	500M-ohm
Dielectric Withstand Voltage	1000 V AC RMS, 60Hz/1min
Time of repetitive use	≥800

Mechanical	
Housing	ABS 94V-0
IDC	PC UL94V-0, Accept 22-26 AWG Solid Wire.
PCB	FR-4 1.6mm(0.06") thickness, 2 layers
Metal Housing	Thickness : 1.6mm, Corrosion Resistant
Contact	Thickness : 0.45mm(0.018")
Contact	Diameter :Phosphor Bronze with gold plating

Ordering Information

Part Number	Description
TT3-VP11-24P	19" Voice RJ 11 Patch Panel 24 Port
TT3-VP11-48P	19" Voice RJ 11 Patch Panel 48 Port